EXECUTIVE ORDER U-R-015-0339 New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engines and emission control systems produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)		
2017	HFPXL06.7CLA	6.7	Diesel	8000		
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION			
Turbocl	nic Direct Injection, Engin harger, Charge Air Cooler Selective Catalytic Reduct Oxidation Cataly	r, Diesel Oxidation ion - Urea, Ammonia	Tractor, Generator Set, and Other Industrial Equipment			

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for non-methane hydrocarbon (NMHC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED	EMISSION STANDARD CATEGORY		EXHAUST (g/kw-hr)					OPACITY (%)		
POWER CLASS			NMHC	NOx	NMHC+NOx	со	PM	ACCEL	LUG	PEAK
130 ≤ kW ≤ 560	Tier 4 Final	STD	0.19	0.40	N/A	3.5	0.02	N/A	N/A	N/A
		CERT	0.001	0.31		0.05	0.02			

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

BE IT FURTHER RESOLVED: That the listed engine family is conditionally certified pending submission of additional test data to verify compliance with useful-life emission standards. The manufacturer has until October 15, 2017 to provide test data to confirm or correct the certification emissions levels on this conditional certification. Failure to resolve concerns by the specified date, shall be cause for the Executive Officer to rescind this conditional certification, in which case all engines covered under this conditional certification would be deemed uncertified pursuant to Health and Safety Code Section 43153 and subject to civil penalties pursuant to Health and Safety Code Section 43154.

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this ______ day of March 2017.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

U-12-015-0339 Allechunt ps 111 3/6/2007

Engine Model Summary Template

Engine Family	1.Engine Code	2.Engine Model	3.BHP@RPM (SAE Gross)	4,Fuel Rate; mm/stroke @ peak HP (for diesel only)	5.Fuel Rate: (lbs/hr) @ peak HP (for dlesels only)	6.Torque @ RPM (SEA Gross)	7.Fuel Rate; mm/stroke@peak torque		9.Emission Control Device Per SAE J1930
HFPXL06.7CLA	F4DFE617H*B	F4DFE617H*B	280 @ 2150	131	N/A	945 @ 1400	178	N/A	DDI ECM TO CAC DOG SCR-u AMOX
HFPXL06.7CLA	F4DFE617G*B	F4DFE617G*B	257@ 2150	122	N/A	861 @ 1400	162	N/A	DDI ECM TO CAC DOC SCR-u AMOX
HFPXL06.7CLA	F4DFE617B*B	F4DFE617B*B	249 @ 2150	118	N/A	839 @ 1400	160	N/A	DDIECM TO CAC DOC SOR-U AMOX
HFPXL06,7CLA	F4DFE617F*B	F4DFE617F*B	240 @ 2150	114	N/A	794 @ 1300	151	N/A.	DDIECM TO CAC DOG SCR-u AMOX
HFPXL06.7CLA	F4DFE617D*B	F4DFE617D*B	225 @ 2150	108	N/A	767 @ 1500	144	N/A	DDIECM TO CAC DOC SCR-4 AMOX
HFPXL06.7CLA	F4DFE617C*B	F4DFE617C*B	205 @ 2150	97	N/A	781 @ 1500	131	N/A	DDIECM TO CAC DOC SCR-u AMOX
HFPXL06.7CLA	F4HFE617B*B	F4HFE617B*B	249 @ 2150	118	N/A	839 @ 1400	160	N/A	DDI ECM TC CAC DOC SCR-u AMOX